



**viprinet®**

#### Technical Specifications

Enclosure format	19" 1,5 U
Dimensions (WxHxD)	435 x 66 x 320 mm
Weight (ca.)	5,1 kg
Power rating	100-240 VAC, 50-60 Hz
Power supply	Integrated IEC socket
Fans: Number / Regulation / Control	2 / ✓ / -
LAN Interface	Gbit Ethernet
WAN module slots	6
Max. power consumption	75 Watt
Typical power consumption	45 Watt
SNMP status / accounting	✓ / ✓
Bonding capacity MBit/s	200

#### Features

- Real bonding of all connection bandwidths with / without TCP optimizing
- Quality of Service / traffic shaping (per WAN module / VPN tunnel)
- NAT and port forwarding
- Monitoring (graphical and remote-syslog)
- Unlimited number of VPN tunnels (SSL / AES)
- Rule-based routing
- Traffic accounting via external server
- Multi-user web administration system

#### Delivery Content

- Multichannel VPN Router 2610
- Power cable
- Manual
- CD with software
- 2 angle brackets for inserting router into 19" rack
- Modules according to ordered choice

## PRODUCT INFORMATION

### MULTICHANNEL VPN ROUTER 2610



This 19"-sized router allows the bonding of up to six different WAN lines into a single, high-performance virtual link. Its maximum bonding capacity is 125 MBit/s. By adding or substituting single hot plug modems, the network structure can be individually adapted to changing requirements. Thus, it offers long-term security of investment for medium sized and large businesses.

The router is particularly robust and persistent. With the included angle brackets, it can be mounted to 19"-racks as well.

For establishing medium sized and large company networks, we recommend the combination with the Multichannel VPN Hub 2000.

## ACCESSORIES

### Hot Plug Modules

- ADSL 2+ Annex A
- ADSL 2+ Annex B
- UMTS / EDGE / HSPA
- UMTS / EDGE / HSPA+
- Euro ISDN
- Fast Ethernet

### Optional Additional Licences

- Streaming optimization
- Viprinet VPN Client