



viprinet®

Technical Specifications

| | |
|--|-----------------------|
| Enclosure format | 19" 1,5 U |
| Dimensions (WxHxD) | 435 x 66 x 320 mm |
| Weight (ca.) | 5,1 kg |
| Power rating | 100-240 VAC, 50-60 Hz |
| Power supply | Integrated IEC socket |
| Working temperature | 0-35° C |
| Fans: Number / Regulation / Control | 2 / ✓ / - |
| LAN Interface | GBit Ethernet |
| WAN module slots | 6 |
| Max. power consumption | 75 Watt |
| Typical power consumption | 45 Watt |
| SNMP Basic / Extended | ✓ / ✓ |
| Bonding capacity MBit/s | 200 |

Features

- Real bonding of all connection bandwidths with / without TCP optimizing
- Quality of Service / traffic shaping (per WAN module / VPN tunnel)
- NAT and port forwarding
- Monitoring (graphical and remote-syslog)
- Unlimited number of VPN tunnels (SSL / AES)
- Rule-based routing
- Traffic accounting via external server
- Multi-user web administration system

Delivery Content

- Multichannel VPN Router 2610
- Power cable
- Manual
- CD with software
- 2 angle brackets for inserting router into 19" rack
- Modules according to ordered choice

PRODUCT INFORMATION

MULTICHANNEL VPN ROUTER 2610



This 19"-sized router allows the bonding of up to six different WAN lines into a single, high-performance virtual link. Its maximum bonding capacity is 125 MBit/s. By adding or substituting single hot plug modems, the network structure can be individually adapted to changing requirements. Thus, it offers long-term security of investment for medium sized and large businesses.

The router is particularly robust and persistent. With the included angle brackets, it can be mounted to 19"-racks as well.

For establishing medium sized and large company networks, we recommend the combination with the Multichannel VPN Hub 2000.

ACCESSORIES

Hot Plug Modules

- ADSL 2+ Annex A
- ADSL 2+ Annex B
- UMTS / EDGE / HSPA
- UMTS / EDGE / HSPA+
- Euro ISDN
- Fast Ethernet

Optional Additional Licences

- Streaming optimization
- Viprinet VPN Client